

# Specifications - MP3200

---

|                                      |   |
|--------------------------------------|---|
| <b>Printing Method</b>               | Line Thermal Dot Printing   |
| <b>Printing Width</b>                | 48mm  |
| <b>Dot pitch</b>                     | 203 dpi   |
| <b>Printing speed</b>                | Max. 70 mm/sec  |
| <b>Bar-code Type</b>                 | JAN13/8, Code39/128, ITF, NW-7, QR & PDF417   |
| <b>Paper</b>                         | Max. Width 58mm, Thickness 60-65 µm, Max. Diameter 50 mm                              |
|                                      | IrDA Version 1.2 (Up to 38.4 Kbps)  |
| <b>Interface</b>                     | RS-232C with optional special cable (up to 38.4 Kbps)<br>Bluetooth wireless interface |
| <b>Sensor &amp; Error monitoring</b> | Paper end, Cover-open, Low battery, Head overheat                                     |
| <b>Optional Mag stripe reader</b>    | Track 1, 2 & 3  |
|                                      | Li-ion battery 2200mAh  |
| <b>Power Supply</b>                  | AC adaptor for charging (output DC 9V, 2.7A) Optional extra                           |
| <b>Battery</b>                       | 40,000 print lines per charge (Characters)<br>Maximum recharge time: 3 hours          |
| <b>Auto power off</b>                | 1-60 minutes (default 10 min.) Software selectable.                                   |
| <b>Weight</b>                        | Approx. 520g (with battery & belt clip, w/o paper roll)                               |
| <b>Dimensions (W x D x H)</b>        | 99 x 139 x 72 mm  |
| <b>Operating environment</b>         | 5 ~ 40 °C   |