

KIO-F21 Self Service Kiosk



Meet the Nexa KIO-F21 kiosk, a smart and slim solution for your business needs. Whether in a restaurant, a retail store, or any other kind of business that requires customer interaction, the Nexa KIO-F21 kiosk can help you streamline your operations and enhance your customer satisfaction.

The Nexa KIO-F21 kiosk has a 21.5" FHD screen with a side panel thickness of only 44mm, making it a perfect fit for any space. It also has a sleek and modern design that will complement your brand image and attract more customers.

With the Nexa KIO-F21 kiosk, you can give customers a quick and easy way to order and pay directly at the kiosk, saving time and improving efficiency.

The Nexa KIO-F21 kiosk is a cutting-edge and innovative choice that will help you increase your sales and profits.



Optional Floor Stand



Intel Quad Core
2GHz CPU



Year Warranty

Specifications

System	Processor	Intel® Celeron® Quad-core Processor J4215 2.0GHz(Fanless)		
	Chipset / BIOS	Intel® Elkhart Lake SoC / AMI		
	Storage	2.5" SATA III SSD 128GB		
	Memory	8GB SO-DIMM, DDR4 2666MHz~3200MHz x 1 (Max 32GB, optional)		
	Graphics	Intel® UHD Graphics for 10th Gen Inte®I Processors		
	OS	Windows 10 IoT Entry		
	Display Type	21" LCD with WLED Backlight (1080 x 1920 resolution) True-Flat Capacitive 10 Point Multi-Touch		
	I/O Interfaces	USB	6 x USB 2.0(Rear Top x 2, Rear Bottom x 4)	
		Serial	6 (DB9 x 3, RJ50(RJ45 x 2, RJ11 x 1) COM1, 3, 5(DB9) : +5V on pin #9, Selectable by BIOS COM2, 4(RJ50, RJ45) : +5V and +12V for Special Devices COM6(RJ11) : USB 2.0 and RS232 with +5V/1A for Card Reader	
		Audio	1 x Audio-out / 3.5mm (Changeable for MIC)	
		Display	1 x DisplayPort (Included 1 x USB 2.0 / Power Delivery +12V) *Can be used for HDMI and DVI, VGA monitor by passive cable.	
		LAN	1 x RJ45 (Base-T 10/100/1000 Ethernet)	
Physical Dimensions		Dimernsion (W x D x H)	Desk Type 330 x 260 x 815 (mm) Stand Type 500 x 400 x 1,691 (mm)	
		Weight	Desk Type 15.7 kg Stand Type 33 kg	
		Environment	Power Suppy	DC 24V/4A (AC 100V~240V, 96W)
			Temperature	Operating: 0 ~ 50°C at 10% to 90% humidity

Nexa KIO_F21 Data Sheet | Rev C | May-23 | © 2023 | Features & specifications subject to change without notice.